

				PACKAGED AIR CONDITIONER STANDARD SPECIFICATIONS				CONTRACTOR :	
								LOCATION :	
								DATE :	
No.	MODEL ITEM				PA-A500G(G,Y)8 / RC-G265X8 (COMP INDOOR)		REMARK		
					INDOOR UNIT	OUTDOOR UNIT			
1	COOLING CAPA.			W	58,140				
				kcal/h	50,000	-			
2	HEATING CAPA.			W	60,000			전기가열기 내장형일 경우	
				kcal/h	51,600	-			
3	UNIT SIZE	HEIGHT	mm	2,190(1,870)	1,022	()는 덕트 사양시			
		WIDTH	mm	1,813	1,350				
		DEPTH	mm	720	710				
4	BLOWER	TYPE	-	SIROCCO FAN	PROPELLER FAN				
		AIR FLOW RATE	CMM	180	140 * 2				
		MOTOR	kW x P	2.2kW X 4P (3.7KW X 4P)	0.21kW * 2 * 2	()는 덕트 사양시			
		EXTERNAL PRESS.DROP	mmAq	0(15)	-	()는 덕트 사양시			
5	NET WEIGHT			kg	357	190 * 2			
6	REFRIGERANT				R-22				
7	REFRIGERANT CONTROL				CAPILLARY				
8	POWER				3PH 220/380/440V 60Hz				
9	COMPRESSOR			TYPE	SCROLL				
				kW	6.75				
10	PIPING SIZE	REF.	GAS	mm	25.4				
			LIQUID	mm	15.88				
		DRAIN		-	1B				
		HOT WATER (STEAM)		mm	2B				

■ ACCESSORY

RECEIVER TANK, ACCUMULATOR, LOW PRESSURE SWITCH, SOLENOID VALVE